




System TEPRO

TEPRO Oil Level Windows - Press Fit



without reflector, size 50

with reflector, size 22



min

- One-step fixation
- Self-locking
- No thread required
- · Only thin machine walls required for fixation
- Absolutely oiltight
- Up to 120° C (version M), up to 70° C (standard)
- From diameters 22 to 300 mm
- NBR (standard), Viton™ (or equivalent FKM seals) or silicon seals
- With or without reflector
- Oil level markings with screen print according to your master
- Pressure up to 0,6 bar, then guard ring

Size = Art. No.	D ₁ + 0,1	D ₂	L,	L ₂	$L_{_{3min}}$	D ₃	L ₄
22 (M)	22,2	25	8,5	7	5	19	10
32 (M)	32	35	8,5	7	5	28	10
38 (M)	38,1	41	8,5	7	5	28	10
50 (M)	50	53	10	8,5	6	28	10
75 (M)	75	78	10	8,5	6	28	10
100 (M)	100	103	10	8,5	6	28	10
150 (M)	150	153	10	8,5	6	28	10
200 (M)	200	203	10	8,5	6	_	_
250 (M)	250	253	12	10	8	—	—
300 (M)	300	303	15	12	10	_	_

standard = acrylic plastic, for temperatures up to 70° C

* M = polycarbonate, for temperatures up to 120° C

** reflector included up to size 38



PL21 9LL

Unit A43 Kingsley Close, Vat GB591551821 Company Number 02906480 Lee Mill Industrial Estate Dun and Bradstreet Number (581590544) www.merlin-industrial.com www.merlinblog.com United Kingdom CALL 01752 690 622 EMAIL info@merlin-industrial.co.uk