



TPH workbenches

The TPH workbench already includes a pair of uprights and one shelf; composing our best selling workstation set. It has its own range of accessories, also in stock, and covering the essential, basic needs of any professional workstation.

Stepless height adjustment

The height of TPH workbenches can be steplessly adjusted from 650 to 900 mm, which makes these benches suitable for work while sitting or standing. The height adjustment of the laminate shelf is between 1080-1550 mm. Load capacity for the bench top is 300 kg and for the shelf 50 kg even load



- Standard and cost-effective workbench with one shelf
- Suitable for a wide range of tasks and environments
- Essential range of accessories for basic needs
- Steel frame with loading capacity up to 300 kg



ACCESSORIES ON PAGE 56

Essential range of accessories available for ergonomic TPH workstation.

Designing TPH workstation



- Stepless height adjustment with allen-key between 650-900 mm.
- Frames are of epoxy powder coated steel in grey RAL 7035.
- Includes a pair of uprights and one shelf

Workbench TPH

| Bench size W x D mm | Shelf size W x D mm | Max load kg | Code | Code ESD |
|------------------------|------------------------|----------------|--------|------------|
| 1200 x 700 | 1200 x 310 | 300 | TPH712 | TPH712 ESD |
| 1500 x 700 | 1500 x 310 | 300 | TPH715 | TPH715 ESD |
| 1800 x 700 | 1800 x 310 | 300 | TPH718 | TPH718 ESD |
| 1500 x 900 | 1500 x 310 | 300 | TPH915 | TPH915 ESD |
| 1800 x 900 | 1800 x 310 | 300 | TPH918 | TPH918 ESD |



Lower shelf for TPH

Not enough space above the workstation? Then utilise the space below. The lower shelf for TP bench simply hangs on the horizontal bars.

| Name | Size W x D mm | Max load kg | Code |
|-------------|------------------|----------------|-----------|
| Lower shelf | 1080 x 500 | 50 | AT120 TPH |
| Lower shelf | 1380 x 500 | 50 | AT150 TPH |
| Lower shelf | 1680 x 500 | 50 | AT180 TPH |

Corner workbench TPH KK

A corner workbench can be used with two TPH benches (with one H-frame pair) to create a 90 ° angle setup. TPH KK unit consists of a worktop, two H-frames and a leg in the middle. Front side 565 mm.

| Bench size W x D mm | Max load kg | Code | Code ESD |
|------------------------|-------------|-----------|---------------|
| 1100 x 1100 | 150 | TPH707 KK | TPH707 KK ESD |
| 1300 x 1300 | 150 | TPH909 KK | TPH909 KK ESD |



Laminate bench top

- 25 mm low pressure laminate
- Light grey surface
- Plastic edging

ESD bench top

- Light grey laminate surface
- Grey edging
- Thickness 25 mm
- Semi-conductive (ESD)



* Workbench with one H-frame pair.



Workbench accessories



Accessories for WB



Upright profiles AL2X

Upright profiles AL2X

| Size W x H mm | Suitable for | Code | Code ESD |
|---------------|--------------|-----------|-----------|
| 1063 x 900 | WB811 | AL2X110 W | AL2X110 W |
| 1489 x 900 | WB815 | AL2X150 W | AL2X150 W |
| 1789 x 900 | WB818 | AL2X180 W | AL2X180 W |

Needed for mounting accessories to WB benches. Includes 2 vertical and 1 horizontal profile. With 3 cable clips (CC8).




Accessory frame AKK

Accessory frame AKK

| Size W x D mm | Suitable for | Code | Code ESD |
|--------------------------|------------------------|--------|----------|
| 730 x 540 | AL2X150 W AL2X180 W | AKK70 | AKK70 |
| 690 x 500 + 690 x 500 | AL2X150 W | AKK150 | AKK150 |
| 690 x 500 + 990 x 500 | AL2X180 W | AKK180 | AKK180 |

The accessory frame divides the space between the upright profiles into 2 modules. AKK frame includes 1 vertical and 1 horizontal profile. Useable height 500 mm.



Shelf ALH

Shelf ALH

| Size W x D mm | Suitable for | Code | Code ESD |
|---------------|--|--------|------------|
| 1073 x 310 | AL2X110 W, combination AL2X180 W + AKK180 | ALH110 | ALH110 ESD |
| 1500 x 310 | AL2X150 W | ALH150 | ALH150 ESD |
| 1800 x 310 | AL2X180 W | ALH180 | ALH180 ESD |

Height adjustable shelf. 25 mm laminated particle board. Load capacity 50 kg. Mount on upright profiles.



Lower shelf AT

Lower shelf AT

| Size W x D mm | Max load kg | Suitable for | Code | Code ESD |
|---------------|-------------|--------------|----------|--------------|
| 828 x 400 | 50 | WB811 | AT110 WB | AT110 WB ESD |
| 1255 x 400 | 50 | WB815 | AT150 WB | AT150 WB ESD |
| 1555 x 400 | 50 | WB818 | AT180 WB | AT180 WB ESD |

Height adjustable lower shelf, 25 mm laminated particle board. Mount between the legs.



Backstop LIST

Backstop LIST

| Size W x D x H mm | Suitable for | Code |
|-------------------|--------------------------------|---------|
| 1400 x 52 x 27 | ALH150, AT150 WB, AT150 TPH | LIST150 |
| 1700 x 52 x 27 | ALH180, AT180 WB, AT180 TPH | LIST180 |

Prevents items from falling off the shelf. Can be fixed on the lower shelf AT or on the shelf ALH.

Divider hoops PDH

| Height mm | Suitable for | Code | Code ESD |
|-----------|--------------|------|----------|
| 400 | ALH | PDH | PDH |

Used in combination with shelf ALH. Comes in sets of 5.



Divider hoops PDH

Perforated panel ARL

| Size W x H mm | Suitable for | Code | Code ESD |
|---------------|---------------|--------|----------|
| 668 x 500 | AKK70, AKK150 | ARL70 | ARL70 |
| 968 x 500 | AKK180 | ARL100 | ARL100 |

Mount on accessory frame AKK. The size of the perforation is 9 x 9 mm, center to center 38 mm.




Perforated panel ARL

Adjustable shelf ASH

| Size W x D mm | Suitable for | Code | Code ESD |
|---------------|-----------------------|--------|------------|
| 660 x 400 | AKK70, AKK150, AKK180 | ASH70 | ASH70 ESD |
| 960 x 400 | AKK180 | ASH100 | ASH100 ESD |

Continuous adjustment for depth, height and angle. Shelf of 25 mm laminated particle board. Lipped front edge. Load capacity 35 kg static load. Mount on accessory frame AKK.



Adjustable shelf ASH

Bin profile BP

| Length mm | Suitable for | Code | Code ESD |
|-----------|------------------------|-------|-----------|
| 685 | AKK 70, AKK150, AKK180 | BP70 | BP70 ESD |
| 985 | AKK180 | BP100 | BP100 ESD |

Aluminium profile for stacking and picking bins. Mount on accessory frame AKK.



Bin profile BP

Swivel arm with tray AKV

| Size W x D mm | Suitable for | Code | Code ESD |
|------------------|-----------------------|--------|------------|
| 460 x 210 (tray) | AL2X upright profiles | AKV400 | AKV400 ESD |

Lockable, angle adjustable steel tray with swivel radius of 360°. Length of swivel arm 590 mm. Max. load 15 kg.



Swivel arm with tray AKV


Component rack EPL

| Size W x D x H mm | Suitable for | Shelves number | Code ESD |
|-------------------|--------------|----------------|-----------|
| 455 x 200 x 290 | AKV | 3 | EPL12 ESD |

Rack with three fixed shelves. Semiconductive epoxy powder coated steel in light grey (RAL 7035). Bins ordered separately, page 54.

Component rack holds:

- 12 stacking bins 1015-4ESD or 12 picking bins 30-1L-4ESD or 6 picking bins 30-2L-4ESD or 6 picking bins 30-23L-4ESD.



Component rack EPL

Document stand WDA

| Size W x H mm | Suitable for | Code | Code ESD |
|---------------|-----------------------|------|----------|
| 440 x 300 | AL2X upright profiles | WDA | WDA ESD |

Document stand A3 with swivel arm. Epoxy powder coated steel: light grey. Arm length 220 mm. Tilt 75°.



Document stand WDA



Bottle holder CH

Bottle holder CH

| Size W x D x H mm | Ø mm | Suitable for | Code | Code ESD |
|-------------------|------|-----------------------|------|----------|
| 110 x 105 x 120 | 80 | AL2X upright profiles | CH | CH |

Practical holder for bottle or cup. Made of black polypropylene.



Recycling material bin PRMB

Recycling material bin PRMB

| Size W x D x H mm | Suitable for | Code |
|-------------------|--------------|-------|
| 530 x 280 x 585 | WB benches | PRMB2 |
| 530 x 280 x 585 | TP benches | PRMB |

The 60 ltr bin with steel brackets has a maximum load of 15 kg and can be positioned on either side or rear of the bench.



Tool holder box PPH

Tool holder box PPH

| Size W x D x H mm | Suitable for | Code |
|-------------------|-------------------|---------|
| 400 x 300 x 140 | WB and TP benches | PPH TXL |

PPH TXL with two blue plastic bins type 3020.



Tool tray PTH

Tool tray PTH

| Size W x D mm | Suitable for | Code |
|---------------|--------------|--------|
| 1000 x 60 | WB benches | PTH100 |

The tool tray guarantees a clean working space, while tools are close to hand.




Support bracket HSB

Support bracket HSB

| Length mm | Suitable for | Code | Code ESD |
|-----------|--------------|--------|----------|
| 1073 | AL2X110 W | HSB110 | HSB110 |
| 1500 | AL2X150 W | HSB150 | HSB150 |
| 1800 | AL2X180 W | HSB180 | HSB180 |

Support bracket of steel for suspending power tools and lighting units. Mount on upright profiles.



Cable tidy WBCT

Cable tidy WBCT

| Size W x D x H mm | Suitable for | Code | Code ESD |
|-------------------|--------------|---------|----------|
| 948 x 64 x 204 | WB811 | WBCT110 | WBCT110 |
| 1375 x 64 x 204 | WB815 | WBCT150 | WBCT150 |
| 1675 x 64 x 204 | WB818 | WBCT180 | WBCT180 |

Mount on leg frame. A cable tidy is standard equipment on WB C and WB EL models.



Cable clip set CC

Cable clip set CC

| Set | Suitable for | Code | Code ESD |
|----------|-----------------------|------|----------|
| 5 pieces | AL2X upright profiles | CC8 | CC8 |

The cable clip set will hold cables etc. securely and neatly in place along the bench frame. The clips locate in the 8 mm profile slot.

Keyboard shelf WKA

| Size W x D mm | Suitable for | Code | Code ESD |
|-------------------|-----------------------|------|----------|
| 500 x 220 (shelf) | AL2X upright profiles | WKA | WKA ESD |

Keyboard shelf with swivel arm. Epoxy powder coated steel. Load capacity 15 kg. Arm length 220 mm.



Keyboard shelf WKA

PC stand CPU

| Width | Height | Suitable for | Code |
|------------|------------|------------------------|------|
| 130-240 mm | 395-500 mm | WB and TP/TPH benches | CPU |
| 340-460 mm | 180-285 mm | SAP, CTR, WTR trolleys | |

An adjustable holder for either vertical or horizontal CPU, to mount underneath the table worktop.



PC stand CPU

LCD bracket MH

| Max load kg | Suitable for | Code |
|-------------|-----------------------|------|
| 15 | AL2X upright profiles | MH |

The quick-release mechanism is equipped with the standard used flat-screen mount 75 x 75 and 100 x 100 for the mounting of all normal flat-screens.



LCD bracket MH

LCD swivel arm MA

| Max load kg | Suitable for | Code |
|-------------|-----------------------|------|
| 10 | AL2X upright profiles | MA |

The quick-release mechanism is equipped with the standard flat-screen mount 75 x 75 and 100 x 100 for the mounting of all normal flat-screens. The arm is double articulated, turns through a radius of 180° and will extend between 95-425 mm from the upright.



LCD swivel arm MA

LCD swivel arm MA2

| Max load kg | Suitable for | Code |
|-------------|-----------------------|------|
| 15 | AL2X upright profiles | MA2 |

The quick-release mechanism is equipped with the standard, widely used flat-screen mount 75 x 75 and 100 x 100 for the mounting of all normal flat-screens. The arm is double articulated, turns through a radius of 180° and will extend between 95-425 mm from the upright.



LCD swivel arm MA2

Tablet bracket MY

| Suitable for | Code |
|---------------|------|
| MH, MA or MA2 | MY |

For 7-10" tablets. Requires either an MH, MA or MA2 swivel arm.



Tablet bracket MY

Power channels CJK

| Dims mm | Suitable for | Code |
|--|-----------------------|-----------|
| Profile 631 | AL2X upright profiles | CJK70 |
| Profile 931 | AL2X upright profiles | CJK100 |
| 3 double sockets (E1) and a switch (E2) | | CJK70 SET |
| Double socket | | E1 |
| Switch | | E2 |
| Automatic fuse 10 A | | E3 |
| Automatic fuse/earth leakage switch 10 A/30 mA | | E4 |
| Emergency-stop-switch | | E5 |
| Data connector/shielded for Cat.6 cable | | E6 |

Can be fitted with a choice of components, ordered separately. All meet with CE requirements. 3 m cable is included. Supplied wired and ready for use. A finished CJK 70 SET includes 3 double sockets (E1) and a switch (E2). Other sets are also available.



CJK70 SET