

# LOW LEVEL SERIES

Zinc Plated Pressed Steel Construction  
Double Ball Race Swivel Head



## Top Plate Fixing



96 Shore A  
Orange Polyurethane  
On Steel

-20°C to +80°C

Dia (mm)	Height (mm)	Plate (mm)	Centres (mm)	Fixing Bolt (mm)	Type	Bearing	Code	Load (kg)	Tread (mm)	Radius (mm)
35	65	60 x 48	48 x 35	6			BZXH35PTBJ	100	27	33

## Loose Stem Fixing



96 Shore A  
Orange Polyurethane  
On Steel

-20°C to +80°C

Dia (mm)	Height (mm)	Stem (mm)	Head Dia (mm)	Type	Bearing	Code	Load (kg)	Tread (mm)	Radius (mm)
35	58	10	46			BZXH35PTBJST10	100	17	31

# LOW LEVEL SERIES

Zinc Plated Pressed Steel Construction  
Double Ball Race Swivel Head



PLATE FIXING



75-200kg



40-50mm

## Top Plate Fixing

Dia (mm)	Height (mm)	Plate (mm)	Centres (mm)	Fixing Bolt (mm)	Type	Bearing	Code	Load (kg)	Tread (mm)	Radius (mm)	Material	Temp Range
50	73	95 x 67	76 x 44	8			BZH632X50NY	75	14 x 2	44	Nylon	-20°C to +80°C
50	73	95 x 67	76 x 44	8			2BZXL50NY	90	15 x 2	48	Nylon	-20°C to +80°C

## Top Plate Fixing

Dia (mm)	Height (mm)	Plate (mm)	Centres (mm)	Fixing Bolt (mm)	Type	Bearing	Code	Load (kg)	Tread (mm)	Radius (mm)	Material	Temp Range
40	64	65 x 65	50 x 50	6			-	-	-	-	Black Nylon	-30°C to +80°C
50	75	65 x 65	50 x 50	6			BZXH50NY	200	28	50	White Nylon	-30°C to +80°C
							BZXH50NYBR	200	28	50	White Nylon	-30°C to +80°C
							BZXHF50NY	200	28	-	White Nylon	-30°C to +80°C